

# R-SCG G/Y Thin Wall Flame Retarded Green Yellow Stripe Tubing



## APPLICATIONS:

SCGS range of tubing is an extremely flexible, flame-Retardant, thin wall, green and yellow striped heat shrink polyolefin tubing especially developed for electrical equipment ground lead applications. The unique dual color striping of green and yellow provides an instant identification for ground wires.

## GENERAL PROPERTIES OF PRODUCT:

- Shrink ratio 2:1
- Flame retarded and self-extinguishing
- For Electrical Insulation up to 600 volts
- Resistance to chemical, copper corrosion and fungus
- UV stabilized
- Meet ROHS Compliance



## SPECIFICATIONS:

**Spec:** MIL-1-23053/5 Class 2 & 3, UL224 125 deg. C VW1, CSA C22.2 No. 198.1 OFT

## PRODUCT DIMENSIONS:

Part Number/Size	Internal Diameter (mm)		Recovered Wall Thickness (mm)	Packing Configurations		
	Supplied	Recovered		Spools	1.2m Lengths	Dispenser Box
SCG 2.5/1.2GY	2.5 mm	1.2 mm	0.44 mm	200 m	600	20 m
SCG 3.5/1.7GY	3.5 mm	1.7 mm	0.44 mm	200 m	500	20 m
SCG 5.0/2.5GY	5.0 mm	2.5 mm	0.56 mm	100 m	250	10 m
SCG 7.0/3.5GY	7.0 mm	3.5 mm	0.56 mm	50 m	200	10 m
SCG 10.0/5.0GY	10.0 mm	5.0 mm	0.56 mm	50 m	100	10 m
SCG 13.0/6.5GY	13.0 mm	6.5 mm	0.69 mm	50 m	120	5 m
SCG 20.0/10.0GY	20.0 mm	10.0 mm	0.78 mm	50 m	65	5 m
SCG 25.0/12.5GY	25.0 mm	12.5 mm	0.86 mm	50 m	40	5 m
SCG 40.0/20.0GY	40.0 mm	20.0 mm	0.96 mm	25 m	20	
SCG 50.0/25.0GY	50.0 mm	25.0 mm	0.96 mm	25 m	15	
SCG 76.0/38.0GY	76.0 mm	38.0 mm	1.27 mm	25 m	10	
SCG 100/50.0GY	100.0 mm	50.0 mm	1.40 mm	25 m	5	

Note: Special sizes available on request.